

## OAK PLANK 2 LAYERS – THICKNESS 15 MM

---

- **Technical features:**

Thickness	15 mm
Support Type	Plywood
Top Layer Thickness	4 or 5,2 mm
Plywood Thickness	11 or 10 mm
Top Layer	Oak
Plywood	Birch
Widths	120 - 140 – 160 – 180 – 200 – 230 mm
Lengths	from 1000 to 2400 mm
Available Selections	Elite, Nature or Country



- **Description of Elite selection:**

Light uniform color. “Live” knots are allowed (diameter max 5 mm). Sapwood, wood hearts, tarps and cracks are not allowed.

- **Description of Nature selection:**

Permissible color alteration within the limits of natural shades of “healthy” wood. “Live” knots (max diameter 30 mm) and “filled” knots (max diameter 20 mm) are allowed. Sapwood, wood hearts, tarps and cracks are not allowed.

- **Description of Country selection:**

All the “healthy” wood shades and any color defects are allowed. “Live” knots (diameter max 50 mm), “dead” knots, “missing” knots (diameter max 30 mm) and cracks are allowed. “Missing” knots and cracks are filled with filler. Sapwoods and wood hearts are allowed. Cracks on the head are only accessible closed (not visible) up to 50 mm long.